

Overhead stirrers



AT - ANALOGICAL



AT - DIGITAL
REMOTE
CONTROLLER




AT - DIGITAL

AT series

- Rod stirrers with continuous regulation of speed. Suitable for routine and continuous works.
- Smooth start and change of the stirring speed.
- Overload protection and over-heat protection functions for motor.

Technical data		AT-M 10	AT-M 20	AT-MD 10	AT-MD 20	AT-MCD 10
Protection class	IP	43	43	43	43	43
Safety class		0	0	0	0	0
Set lecture values		analogical	analogical	digital	digital	digital
Variable speed	rpm	200-3000	200-3000	200-3000	200-3000	200-3000
Max couple torsion spindle	ncm	85	145	85	145	30
Max Ø probe insertion	mm	10	10	10	10	10
Max stirring capacity with H ₂ O	lt	10	20	10	20	10
Max viscosity	mPas	10000	50000	10000	50000	10000
Absorbed power	W 83/120	75	120	75	120	30***
Dimension LxWxH	mm	90x145x180	90x145x180	90x145x180	90x145x180	90x100x180
Power	V/Hz	230/50-60	230/50-60	230/50-60	230/50-60	230/50-60
Weight	kg	4,5	5,3	4,5	5,0	3,5
Item		605.0150.10	605.0150.12	605.0150.18	605.0150.20	605.0150.15

Accessories for overhead stirrers



Stainless steel stirring rods

Item	Photo n°	Rotor mm length x H mm	Ø rod mm	Overall length mm
605.0152.02	1	50x10	7	300
605.0152.03	2	50x20	7	300
605.0152.04	3	70x50	7	300
605.0152.05	4	45x40	8	350
605.0152.06	5	100x10	7	300
605.0152.07	1	100x20	7	300
605.0152.08	6	50	7	300
605.0152.10	4	90x80	8	350



Stainless steel stirring shafts - PTFE coated

Item	Rotor mm length x H mm	Ø rod mm	PTFE thickness	Overall length mm
605.0152.12	90x20	6,5	1,5	450
605.0152.13	90x20	6,5	1,5	600



Stainless steel stirring shafts with rigid paddle - PTFE coated

Item	Rotor mm length x H mm	Ø rod mm	PTFE thickness	Overall length mm
605.0152.15	80x12	6,5	1,5	450
605.0152.16	80x12	6,5	1,5	600



Stainless steel U-shaped stirrer shafts - PTFE coated

Item	Rotor mm length x H mm	Ø rod mm	PTFE thickness	Overall length mm
605.0152.17	60x40	6,5	1,5	350
605.0152.18	60x40	6,5	1,5	450
605.0152.19	80x50	6,5	1,5	450



Stainless steel fan shaped stirrer shafts - PTFE coated

Item	Rotor mm length x H mm	Ø rod mm	PTFE thickness	Overall length mm
605.0152.23	38	6,5	1,5	300
605.0152.22	24	6,5	1,5	300

Supports e clamps

Item	Description
263.8350.20	Support opening 130x280 mm with one rod ØxH 12x600 mm
263.8350.22	Support opening 180x460 mm with one rod ØxH 15x750 mm
263.8350.72	Support opening 230x600 mm with three rods ØxH 15x1000 mm
146.2900.41	Claw clamp with maximum opening Ø18 mm for rods

